

Competing Model

SMS car# _____

Bodies

- _____ Complete & neat appearing
- _____ 3 windshield bars in front of driver
- _____ Firewall and floorboards mandatory
- _____ Rear spoiler 5" max in height & width of deck
- _____ Hood scope 6" maximum in height
- _____ Front & rear bumpers mandatory

FRAME

- _____ 4" minimum height to ground
- _____ 108" wheel base minimum
- _____ 78" outside wheel to outside wheel

Roll Cage

- _____ All welds complete and in good condition
- _____ Minimum 6 point cage
- _____ Minimum one cross bar in top halo
- _____ Protection of feet mandatory
- _____ 3 bars plated on drivers door
- _____ Padding on all cage bars in drivers area

Wght.

- _____ Minimum weight 2500 Lbs.
- _____ 56% maximum left side percentage
- _____ All ballast weights securely fastened
- _____ Painted white
- _____ Car number on weights

Brakes

- _____ All four wheels
- _____ Steel OEM calipers only

Fuel Cell

- _____ 32 gal. Maximum in a steel container
- _____ Tank must have two straps 2"x1/8"
- _____ 6" ground clearance & 4" in front of rear bumper

Fuel system

- _____ Mechanical fuel pump OEM type
- _____ If fuel line thru drivers compartment, enclosed
- _____ 1 Gas filter, Non-glass allowed

Engine

- _____ Any American OEM
- _____ No aluminum heads or blocks
- _____ GM 23 degree heads only
- _____ No total dry sumps allowed

Cooling

- _____ Overflow canister, 1 quart capacity mandatory

Numbers

- _____ 20" roof numbers
- _____ 20" door numbers

Electrical System

- _____ Self starter in stock position
- _____ Battery fastened properly
- _____ Master kill switch in reach of driver
- _____ Electronic ignition allowed

Exhaust System

- _____ Headers are mandatory

Transmission

- _____ OEM type with forward & reverse in operation
- _____ No 5 spds., in/out box's, or quick changes allowed
- _____ working disc-type or cone-type clutch
- _____ Scatter shield mandatory

Drive shaft

- _____ Steel type only
- _____ Painted white
- _____ 2"x1/4"/ 1" tubing loop 6" behind front U-joint

Rear end

- _____ Any approved OEM car or truck may be used
- _____ No aluminum allowed except blocks, caps, flanges
- _____ No quick change allowed

Suspension Front

- _____ Lower A-arms must be stock in stock location
- _____ No fabricated spindles
- _____ Front sway bar optional. Must be OEM steel

Wheels

- _____ 8" wide steel only
- _____ Minimum 1/2" studs on all four wheels

Tires

- _____ SMS approved McCreary G60, KK704 IMCA or Hoosier G60-15 IMCA only

Safety

- _____ Aluminum seat with head rest required
- _____ Helmet Snell SA95 or newer with eye protection
- _____ SFI full fire suit required
- _____ (If one layer, nomex underwear required)
- _____ SFI Neck brace, gloves, & shoes required
- _____ 16"x20" window net required (ribbon type) or
- _____ Arm restraints
- _____ Net latch on top front
- _____ Five point safety belt required not older than 3 yrs.
- _____ Safety belts properly secured
- _____ 3# or better fire extinusher properly mounted
- _____ 10# or better fire extinguisher in pit
- _____ Tow hook or chain, front and rear

Tech Date _____

Tech Official _____

Retech Needed YES _____ NO _____

Drivers signature _____

Comments _____

